


*DSPeaker*

Anti-Mode™ X2

User's Guide



## Recycling information

Anti-Mode™ X2 is marked according to the **Waste Electrical and Electronic Equipment Directive**. There are take-back systems in place that help to preserve nature and natural resources when products are disposed of appropriately. If you need to dispose of this product, use the take-back system that has dedicated collection facilities for electronic equipment. Do not put the product into household waste disposal!



Anti-Mode™ X2 is manufactured using parts and processes that follow the EU directive of the Restriction of the use of certain Hazardous Substances in Electrical and Electronic Equipment (RoHS).

## Safety Instructions

- The unit shall not be exposed to dripping or splashing of liquids and no objects filled with liquids should be placed on the unit.
- Anti-Mode™ X2 has been designed for normal indoor use. Use of the device outdoors, in humid or other extreme environments, may cause reduced performance.
- Anti-Mode™ X2 is intended to be used with cables of up to 3m in length. With longer cables, observe electrostatic discharge precautions when connecting or disconnecting them to avoid damage to equipment. Longer cables may also be susceptible to electromagnetic interference.
- **CAUTION:** The remote control contains two AAA batteries. Only replace it with the same type and in the correct orientation!



### **WARNING: Do not ingest battery, Chemical Burn Hazard!**

Keep batteries out of reach of children and dispose of the used battery appropriately. If a battery is swallowed, it can cause severe internal burns in just 2 hours and can lead to death. If you think batteries might have been swallowed or placed inside any part of the body, seek immediate medical attention

If the battery compartment does not close securely, stop using the remote control and keep it away from children.

- When the unit is in stand-by mode, the display is turned off.
- **CAUTION:** The power supply shipped with the unit is 12VDC 1.6A with 2.1mm/5.5mm connector, center positive. Only connect power supplies with specifications of 12VDC and 0.6A or higher.

## Table of Contents

1. Overview.....	4
What's included in the box.....	4
Remote Control Layout.....	4
Basic Information.....	4
Connections.....	4
Front Panel.....	5
Rear Panel.....	5
Home Screen.....	6
Selecting Input.....	6
Adjusting Volume.....	6
Standby.....	6
Tone Control.....	7
By-Pass Mode.....	7
Subwoofer Output Level.....	7
Sound Profiles.....	7
Menu.....	8
2. Calibration.....	9
3. Hints and Tidbits.....	10
4. Firmware update.....	11
5. Manufacturer.....	11
Contact.....	11
6. Technical Specifications.....	12

## 1. Overview

### What's included in the box


- ✓ The Anti-Mode™ X2 unit
- ✓ A power supply for your country / region
- ✓ A calibration microphone
- ✓ An infra-red remote controller (with batteries)
- ✓ This guide

### Not included

- ✓ USB Type-C cable is not included

### Remote Control Layout

The remote control layout is depicted on the right. When this guide references a button, it usually refers to a press of the corresponding button. ● represents the center button (Ok / Confirm).




### Basic Information

Anti-Mode™ X2 is an automatic room & speaker optimizer with a preamplifier function. Running the automatic calibration procedure using the provided microphone is required to utilize the optimization feature and to establish the correct speaker configuration when a subwoofer is used. See Chapter 2 Calibration on page 9 for details.

### Connections


Connect the left and right outputs to a pair of powered speakers or to your amplifier. If you have a subwoofer, connect it to the "sub" output connector. Up to 3 digital audio sources can be connected: Optical S/PDIF using Toslink, USB Audio 1.0 using USB-C, and Coaxial S/PDIF. If an analog audio source is connected to the "Line In" inputs, the Coaxial S/PDIF connector can not be used at the same time.

Then connect the power supply to the wall socket and the plug to the Power input of the Anti-Mode X2. The unit will automatically start and show "X2" on the screen. After that "0.0" is shown shortly if there is no calibration data. "2.0" or "2.1" is shown otherwise, depending on the mode chosen in a previous calibration.




If your amplifier doesn't have a gain setting or it is set quite high, remember to check the volume setting of the Anti-Mode X2 before proceeding. The default volume is -40dB, you may need to increase it for normal operation.

## Front Panel



- (1) Microphone connector with insertion detection
- (2) Matrix display
- (3) IR receiver





## Rear Panel




- (1) Power supply connector, 12VDC 0.6A - (2.1mm/5.5mm, center positive)
- (2) USB host port for firmware update using a USB memory stick.
- (3) USB audio device connection (for USB Type-C cable). Up to 96kHz 24-bit stereo linear PCM.  
**Notice:** The audio input must be selected to be USB in the Anti-Mode X2 for the computer to be able to discover the device.
- (4) Subwoofer output (connection optional)
- (5) Right analog output
- (6) Left analog output
- (7) Right analog input
- (8) Left analog input / Coaxial S/PDIF input  
**Notice:** Stereo analog input and coaxial S/PDIF inputs are mutually exclusive.
- (9) Toslink Optical S/PDIF input

**Notice:** You can connect CD/DVD players, TVs, media servers, and other audio sources to the digital inputs as long as they provide stereo uncompressed PCM audio up to 192kHz / 24 bits. Compressed formats are not supported.


## Home Screen

Home Screen is the default view of the user interface. It indicates the selected input and volume. An alternative view displays the current sampling rate for the digital audio sources (or three dots for unspecified rate) and a signal level indicator. To select the alternative view, press  and  on the remote controller. To select the default view, press  and .



In the default view, the volume level is displayed as decibel attenuation. "00" represents the maximum and "-70" represents the smallest value possible. Please note that use of tone controls (or mismatch in detected speaker levels) may result in reduced maximum volume available.



In the alternative view example, "C" indicates the coaxial input, "96" indicates 96kHz rate. If all 10 dots in the signal level bar are lit, the signal is at maximum level. Each dot represents 3 dB. If no dots are lit, the signal level is -30 dB or lower.




## Selecting Input


Use  and  to select the active input. This function is available in the home screen. The selected input becomes active when the unit returns to the home screen.

Abbreviation	Mnemonic	Full Name
A	ANA	Analog stereo input
O	OPT	Optical S/PDIF (Toslink) up to Stereo 192kHz / 24 bits
C	COX	Coaxial S/PDIF up to Stereo 192kHz / 24 bits
U	USB	USB Audio (USB-C) Stereo PCM 48kHz or 96kHz / 24 bits


## Adjusting Volume


Use  and  to adjust volume. This function is available in the home screen.

Press  to mute the output. Press any button to return to normal volume.



## Standby

 switches the unit from active to a low-power stand-by state and vice versa.







## Tone Control

ⓘ opens the real-time tone adjustment. You can adjust bass, midrange, and treble according to your personal preference. Use ⬅ and ➡ to select a region to adjust. Use + and - to adjust filter gain in the chosen region.


Keep ● pressed to fine tune the parameters of each filter. Bass and Treble filters support adjustable range. Use ⬅ and ➡ to make the range narrower or wider. Press ⓘ or ● to accept the new value, or ⏻ to cancel the adjustment.

The mid-range filter supports user-selectable range and also a variable center frequency. After choosing the range, at the "Fc" prompt, use ⬅ and ➡ to select a new center frequency. Target frequency is shown in kilohertz (kHz) unit on the display, e.g. "1.5" means a center frequency of 1500 Hz. Press ⓘ or ● to accept or ⏻ to cancel the adjustment.




## By-Pass Mode

Pressing ⓘ and then 🎧 enters a bypass mode. In this mode the Anti-Mode™ room correction is not active. Some enhancements made by the system remain active. These include the crossover between subwoofer and main channels in the 2.1 configuration and speaker level matching. Press any button to leave the bypass mode, then ⓘ or ● to return to the home screen




## Subwoofer Output Level

Pressing ⓘ and then 🎧 allows to change the relative subwoofer level. This setting is only relevant if you have calibrated with the 2.1 configuration. Pressing 🎧 again returns to the tone control view, then ⓘ or ● returns to the home screen.









## Sound Profiles


Anti-Mode X2 supports 3 sound profiles that can be used to store different settings for different situations. You can switch between the profiles in real time by pressing the 🎧 button. Use the + and - to select a profile when prompted and ● to confirm.




Each sound profile can store different room calibration data, tone control preference and subsonic filter.


## Menu


Press  to enter the menu. Press  and  to select between menu items, and  to change its value. Press any other button to close the menu, but note that  chooses the default home screen and  chooses the alternative home screen.









 to return




 to adjust →





 /  or  /  to adjust brightness from 0 to 4.  to return.





 pressed →








 pressed down for 4 seconds until the settings are reset and "OK" is briefly displayed.



 to adjust →



 /  or  /  to toggle infrasonic filter on / off.  to return.



## 2. Calibration

Anti-Mode™ X2 features a powerful and automatic Anti-Mode™ algorithm, which measures and corrects the combined response of the connected speakers, optional subwoofer, and the room, producing a result without undesirable peaks in the response.







During the calibration process the Anti-Mode algorithm measures the acoustic environment by playing various tones through your audio system. This will take a few minutes to complete.





The measurement process is designed to be resilient against background noise, but it can be beneficial to choose a moment when the listening room is relatively quiet. It is also a good idea to turn off any noisy equipment such as air conditioning for the duration of the measurements.

### Before the calibration

- Fix the microphone firmly in place so that the microphone capsule end is at the center of the primary listening position, at about ear height.
- If your system features a subwoofer that has an adjustable low-pass filter, it is good to disable the filter, or set the cut-off frequency to the maximum value. With Anti-Mode the best place for a subwoofer is near the corner of the room.
- Make sure your active speakers or power amplifiers and/or subwoofer are connected to the correct outputs of the Anti-Mode X2 and turned on.
- It is good to adjust the gain of all connected speakers and subwoofer so that the main speakers and subwoofer are approximately equally loud.

### Running the calibration

- Turn on the Anti-Mode X2 unit. Connect the microphone cable to the microphone input at the front panel. The unit enters the calibration mode automatically.
-  /  to choose the system configuration "2.0" for stereo or "2.1" for stereo with a subwoofer and press  .
- Noise starts playing and you can adjust the calibration volume using  /  . The volume setting is shown as a small bar at the top and the sound pressure level picked up by the microphone as a larger bar at the bottom. Adjust the level until the bottom bar reaches the vertical line on the left of the + sign, then start calibration with  .
- The calibration process performs several frequency sweeps. The number of sweeps depends on the chosen system configuration. After the calibration is finished, the display shows "MIC v" to prompt you to remove the microphone.



Congratulations, your system has been optimized! Now it is a good time to put on some of your favorite music and enjoy the improved sound.

**Notice:** The automatic calibration process targets a balanced overall sound, with slightly elevated response towards the low bass region. The response can be adjusted in multiple ways to suit your personal taste.



**FOR BEST RESULTS:** When calibrating a system with a subwoofer, set the built-in lowpass filter of the subwoofer to bypass or to the highest available cutoff frequency. With Anti-Mode the best place for a subwoofer is near a corner of the room.



**PLEASE NOTE:** After Anti-Mode gets rid of room resonances, it may appear that the result sounds good, but is lacking in bass. You may have grown used to the exaggerated bass response caused by room resonances. Listening for a while will accustom you to the new more balanced sound.

If you feel that you need to increase the overall bass level, you can adjust the subwoofer output level or use tone controls.



## 3.Hints and Tidbits

This chapter fills this page with some more or less useful trivia about the product, most useful first.

- ✓ In the 0.0 uncalibrated mode, the subwoofer output will reproduce the low-passed version of the stereo outputs. There is no cross-over in this mode.
- ✓ In the 2.1 mode, the cross-over frequency is 80Hz. (Adjustment will be possible in a later version.)
- ✓ You can connect more than one subwoofer using daisy-chaining or a Y-splitter. The Anti-Mode calibration is only concerned about the combined response of all of the speakers, subwoofers, and the room. Use the same volume setting in each sub, you do not need to adjust them to appear equally loud at the listening position. Only their combined response with the room matters.
- ✓ When there is no S/PDIF signal detected while the OPT or COX input is selected, the alternative home screen shows three dots.
- ✓ You can select the ANA input while coaxial is connected and active without ill effects. If you have the right analog input connected you can switch between right-channel-only analog mode and coaxial two-channel mode. A more useful idea is to have an external RCA switchbox. (You can also select the COX input while the stereo analog input is active without ill effects.)
- ✓ Infrasonic, Bass tone controls, and cross-overs are second-order filters, Treble tone controls are first-order filters.

## 4. Firmware update

The firmware of Anti-Mode™ X2 is updated using a USB memory stick.

- Download the firmware file ( FIRMWARE.X2 ) and copy it to the USB memory stick into its root directory. Make sure the USB memory is using the FAT filesystem format. Some sticks are formatted with the exFAT filesystem, which is not supported.
- Put the Anti-Mode X2 unit to standby with .
- Attach the USB stick to the "SERVICE" USB port on the rear panel of the X2.
- Turn on the Anti-Mode X2 with  and wait until the system automatically installs the firmware. Alternatively, switch off and then on by disconnecting and connecting the power plug.
- Do not remove the USB stick during the update process. After finishing installation the system reboots, and the home screen is displayed. Now the USB stick can be removed.

The firmware is not updated if the unit already contains the same version of the firmware. In this case, after checking the contents of the USB stick the unit will start normally.

If you encounter any problems during the update, make sure the USB stick is properly connected and contains the firmware file. If the problem persists, try copying the firmware file again on a different USB memory stick. Make sure the USB memory is using the FAT filesystem format.

Some USB memory sticks may not be compatible with the firmware update.

## 5. Manufacturer



VLSI Solution / DSpeaker  
Hermiankatu 8  
FIN-33720 Tampere  
FINLAND

Email: [info@dspeaker.com](mailto:info@dspeaker.com)

## Contact

Website: <http://www.dspeaker.com/>

Technical Support: [support@dspeaker.com](mailto:support@dspeaker.com)

Sales Support: [info@dspeaker.com](mailto:info@dspeaker.com)

## 6. Technical Specifications

### Interfaces

- Analog stereo RCA input or 1 coaxial S/PDIF digital input (mutually exclusive)
- 1 optical S/PDIF digital input
  - S/PDIF: 16 to 24 bits PCM, 32 / 44.1 / 48 / 88.2 / 96 / 176.4 / 192 kHz
- USB Audio input (USB Type-C)
  - USB Audio 1.0 stereo 24-bit 48kHz / 96kHz PCM (no drivers required)
- Analog stereo RCA output, analog subwoofer RCA output
- Microphone input
- IR receiver for remote control
- Service USB port for firmware update

### Analog Specifications (typical)

- Frequency Range (analog to analog): 5Hz to 22kHz
- Analog input: 2.3 Vrms (max), SNR 100dB, THD (-6dB level) < 0.002 %
- Stereo output: 2.2 Vrms (max), SNR 107dB, THD (-6dB level) < 0.0015 %
- Subwoofer output: 2.3 Vrms (max), SNR 100dB, THD (-6dB level) < 0.03 %
- Power consumption: active 1.5W, stand-by: 0.1W

### Firmware Highlights

- Anti-Mode™ 3 room calibration algorithm
- Cross-over for speakers and sub(s), automatic balance
- Extensive tone controls
- Firmware update using a USB memory stick

### Mechanical

- Unit Weight: 0.3 kg
- Unit Dimensions: 126mm (width) x 80mm (depth, without cables) x 28mm (height)
- Measurement microphone and remote control included